

a moveable-side clamping portion slidably arranged with the guide rail having a second pair of clamps for clamping an other end of said wire harness; and

clampers, arranged to shift one of said first pair of clamps and one of said second pair of clamps in a radial direction of said wire harness to clamp the wire harness, so that when said movable-side clamping portion is moved towards the fixing-side clamping portion said wire harness is compressed and wires disposed therein are loosened.

201
Please amend Claim 9, as follows:

9. (Amended) A wire harness loosening jig in combination with a wire harness comprising:

- a base plate;
- a fixing-side clamping portion on the base plate having a first pair of clamps for clamping one end of a wire harness;
- a guide rail on said base plate extending in a longitudinal direction of said wire harness, when said wire harness is arranged in said wire harness loosening jig for loosening;
- a moveable-side clamping portion slidably arranged with the guide rail having a second pair of clamps for clamping an other end of said wire harness; and
- clampers, arranged to shift one of said first pair of clamps and one of said second pair of clamps in a radial direction of said wire harness to clamp the wire harness;

wherein said movable -side clamping portion is movable towards the fixing-side clamping portion, so as to compress said wire harness and loosen wires disposed therein, by a driving

202

09/621,138

mechanism including a screw shaft rotatably supported by a bearing on the side of the base plate, a motor for driving the screw shaft, and a lever for driving the motor.

